

## IDH1000/1300



The IDH1000/1300 is a powerful self contained heating solution engineered to provide up to 1,000,000 BTU/hr of heat for the most harshest and remote environments. Includes 2 powerful IDH500QR heaters that each provide 4800 CFM & 3.5" of static pressure.

- \*Slide system for serviceability
- \*Large storage capacity for ducts & tools
- \*Dual axle, shore power, & multiple duct options
- \*Removable grip fenders

## IDH1000:

•Full four-point lifting frame.

•220 US gallon tank with environmental spill containment & forklift pockets. IDH1300:

 Long run time with 300-gallon dual walled tank & forklift pockets. No 4 point lifting frame.

## IDH500TL

The IDH500 units are now available on a tow-able trailer with a 245 gallon tank. The robust trailer has a 7000 lb torsion axle with swivel hitch for smaller footprint on a job site. The tank is double walled with 115% containment. Duct bars for easy duct storage.



SPECIFICATIONS	IDH1000/1300	IDH500TL
BTU/hr	1,000,000	500,000
Static pressure	7" total	3.5"
CFM	9600 total	4800
Generator	Stamford or alternate	Stamford or alternate
Engine	Deutz or alternate	Deutz or alternate
Fuel Capacity	225/300 US Gal	245 US Gal
Total run time	27/42 hours approx.	60 hours approx
Containment	N/A	115%
Pass thru doors	Optional	Optional
Certifications	Constant and the second s	C us